PVA Drywall Interior Primer GL1050-1200

DESCRIPTION

GLIDDEN™ PVA Drywall primer & sealer is a water-based, fast-drying primer and sealer formulated for use on new drywall. It can be applied with a brush or roller for use under latex or alkyd paints on properly prepared new or previously painted drywall, concrete block and brick. **GLIDDEN™ PVA Drywall** primer & sealer dries quickly and sands easily. It is ideal for use on new and existing residential construction and commercial structures.

FEATURES

- Easy application
- Fast drying
- High hiding
- Easy soap and water clean-up
- Low odor
- Low VOC

COMPOSITION

- Vinyl-Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

SPECIFICATION DATA

Color:
White (tintable, limit 4 oz/gal)

Finish: Eggshell
Flat, 3 - 9 units @ 85º

Clean-up Solvent:
Soap and water

Density:
9.88 lbs/gal (1.19 kg/L)

VOC:
50 g/L (0.42 lbs/gal) maximum

Solids:
Volume - 16% +/- 2%
Weight - 28% +/- 2%

Practical Coverage:
Apply at 250-300 sq ft/gal (6-7 m^2/L). Actual coverage may vary depending on substrate and application method.

Recommended Film Thickness:
5.3 - 6.4 mils wet
0.8 - 1.0 mils dry

Flame Spread Rating:
Class A (0-25) on non-combustible surfaces

Flash Point:
None

Dry Time 77°F (25°C) & 50% RH:
To touch - 30 minutes
To recoat - 2 hours

Shelf Life:
1 year minimum - unopened

9 FINISHES PAINTING (09900)

SURFACE PREPARATION

PREPARING PAINTED SURFACES FOR A PROFESSIONAL FINISH

Spackle holes or cracks • Lightly sand glossy areas.

Make sure all areas are clean, sound and free of flaking paint or all substances such as oil, grease, dirt…anything that will get between your surface and your primer • Wash mildewed surfaces with a solution of 16 oz (473 mL) liquid household bleach and two oz (59 mL) non-ammoniated liquid detergent per gallon (3.785 L) of water • Rinse well with clean water • Allow to dry 24 hours • Apply **GLIDDEN PVA Drywall** primer & sealer to properly prepared previously painted surfaces.

IT'S TIME TO PRIME - PREPARING UNPAINTED SURFACES

WALLBOARD - Joint compound must dry for two days before you prime with this product.

WOOD – Sand lightly to a smooth surface, then prime with acrylic primer GL3210.

CONCRETE, PLASTER, MASONRY AND STUCCO - Cure for 30 days before painting. "Slick poured" or pre-cast concrete needs chemical cleaning or a light sandblasting. Thoroughly rinse with water and allow to fully dry. Remove loose aggregate and prime with this product or acrylic primer GL 3210. For concrete block, fill with a **GLIDDEN** block filler. Prime plaster with acrylic primer GL 3210.

GALVANIZED METAL AND ALUMINUM - Clean off oils, then prime with acrylic primer GL 3210 or a metal primer.

STEEL **-** Prime with a metal primer.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DIRECTIONS FOR USE

QUALITY TOOLS FOR A QUALITY JOB

Use a ⅜" - ½" nap roller and a nylon or polyester brush/paint pad.

LET'S GET PAINTING

Mix thoroughly • Apply at package consistency • Do not thin • For airless spray application, use .015-.017" tip. Adjust pressure as needed • Apply generously, no overspreading. For best results, use with a **GLIDDEN** topcoat. Follow paint can application instructions.

LET'S CLEAN UP

Clean hands and tools with warm, soapy water • Clean spills right away with a damp cloth.

PRECAUTIONS

WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. CONTAINS CRYSTALLINE SILICA WHICH CAN CAUSE LUNG CANCER AND OTHER LUNG DAMAGE IF INHALED. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. For emergency information call (800) 545-2643. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID**: For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention**. If swallowed, **get medical attention immediately**. If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.**

DS6-0506

SHIPPING

FREIGHT CLASSIFICATION:
Paint, Freezable

PACKAGING:
1 gallon (3.785 L)
5 gallons (18.925 L)

FLASH POINT:
None

AkzoNobel
Akzo Nobel Paints LLC, Strongsville, Ohio 44136

Glidden
1-800-GLIDDEN • www.glidden.com

LIMITATION OF LIABILITY To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.