9 FINISHES PAINTING (09900)



Advanced Waterproofing Finish FLD150

DESCRIPTION

Flood® Advanced Waterproofing Finish is a translucent exterior wood finish that's designed to restore the rich, warm appearance of natural wood. Flood Advanced Waterproofing Finish provides good protection against moisture and ultraviolet rays. Builds a film for premium durability and penetrates for excellent adhesion, resulting in a long-lasting finish that resists cracking, peeling and flaking and provides a mildew-resistant coating.

WHY USE

- A premium oil-based wood finish that protects and beautifies exterior wood
- Flood's Climate Guard[™] technology protects against exterior wood's two biggest enemies – water and sun
- Transparent iron oxides effectively absorb and block the sun's harmful rays
- Advanced formula that provides excellent durability and adhesion to the wood surface

WHERE TO USE

- · For exterior use only
- All new or weathered exterior wood that is porous enough to accept a finish
- · Exterior decks, fences, siding and furniture

COMPOSITION

- Acrylic Resin
- Not manufactured with lead or mercury containing materials

SPECIFICATION DATA

Color:

Cedar, Redwood & Natural (tintable)

Clean-up Solvent:

Soap & Water

Density:

8.38 lbs/gal (1.0 kg/L)

VOC:

250 g/L (2.08 lbs/gal) maximum Refer to MSDS for regulatory VOC content of complete product line.

Solids:

Volume - 26% +/- 1% Weight - 28% +/- 1%

Practical Coverage:

Apply at 150 - 250 sq ft/gal (4-6 m²/L) Actual coverage may vary depending on the type, age and texture of the wood and application method.

Flash Point:

None

Dry Time 77°F (25°C) & 50% RH:

To touch - 4 hours

To light foot traffic - 24 - 48 hours
To replace furniture - 72 hours
Low temperature, high humidity or poor
ventilation will increase these times. Avoid
heavy abrasions immediately following
application.

Shelf Life:

2 years maximum - unopened



SURFACE PREPARATION

GENERAL SURFACE PREPARATION: Proper surface preparation is essential for the warranty to apply – see side of label for warranty details. All wood surfaces must be thoroughly clean, dry and free of dirt, grease, grime, mildew and previous coatings. Clean with Flood Wood Cleaner/Brightener Concentrate. To remove mildew, clean with a solution of 4 ounces of non-ammoniated detergent (TSP), 1 quart of outdoor bleach and 3 quarts of fresh water. Allow this solution to remain on the surface for 10-15 minutes, then rinse thoroughly with fresh water. DO NOT MIX BLEACH WITH Flood Wood Cleaner/Brightener Concentrate.

NEW WOOD - Many types of wood (such as redwood, red cedar, mahogany, douglas fir, etc.) contain a water soluble material which tends to migrate to the surface and discolor the finish, especially noticeable when using white or light colors. The discoloration is not harmful and can usually be removed with Flood Wood Cleaner/Brightener Concentrate. You may also allow new wood to weather for six months to a year before Finishing. After wood has weathered, clean with Flood Wood/Cleaner and Brightener then apply finish. New wood has a hard, shiny surface called mill glaze that prevents maximum adhesion of a finish – to reduce this mill glaze and open wood so it can accept a finish, treat surface with Flood Wood Finish Remover, using 1 quart of Flood Wood Finish Remover per 1 gallon of water. Rinse thoroughly and allow

wood to dry 24 - 48 hours, or to have a moisture content of 18% or less before finishing.

WEATHERED UNCOATED WOOD - Clean to remove dirt, grime and mildew with Flood **Wood Cleaner/Brightener Concentrate**. Rinse thoroughly and allow wood to dry 24 - 48 hours, or to have a moisture content of 18% or less before finishing.

PREVIOUSLY COATED WOOD - Remove finish with Flood **Wood Finish Remover**. Follow Flood **Wood Finish Remover** label directions for proper application method. Sand, scrape, or wire brush loose, flaking or peeling finish. Pressure wash to remove excess dirt and other contamination. Allow wood to dry 24 - 48 hours, or to have a moisture content of 18% or less before finishing.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DIRECTIONS FOR USE

APPLICATION:

CAUTION: Surfaces are slippery when wet. Use caution when walking on wet surfaces during application.

Test wood for absorbency by sprinkling water on the surface – if water is absorbed within 30 seconds – 2 minutes, depending on climate, the surface is ready for finishing. If water is not absorbed, wait 30 days and re-test.

- 1. Before starting, test your color choice on a small area.
- Buy sufficient product for the whole job and intermix all product together before starting to avoid color variance.
- 3. Stir before and periodically during application.
- 4. Do not thin.
- 5. Apply between 50° F (10° C) 90° F (32° C).
- Do not apply in direct sunlight, if rain, snow, heavy dew or low temperatures below 40° F (4° C) are expected within 48 hours.
- 7. Apply with synthetic brush or roller backbrush if rolled.
- 8. Apply an even coat, avoiding heavy application.
- 9. If the first coat is absorbed within 20 minutes, a second

coat should be applied.

- Apply second coat once first coat is absorbed and before it has dried to touch.
- 11. TWO COAT APPLICATION IS RECOMMENDED FOR OPTIMAL PERFORMANCE.

COVERAGE:

Apply at 150-250 sq ft/gal (4-6 $\,\mathrm{m}^2/\mathrm{L})$. Actual coverage may vary depending on the type, age and texture of the wood and application method.

DRY TIME @ 77°F (25°C) & 50% RH:

Dries to touch in approximately 4 hours. Dries to light foot traffic in 24 - 48 hours. Wait 72 hours before replacing furniture. Low temperature, high humidity, thick films or poor ventilation will increase these times. Avoid heavy abrasions immediately following application.

CLEAN-UP AND STORAGE:

Clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth. **KEEP FROM FREEZING.**

PRECAUTIONS

WARNING! HARMFUL OR FATAL IF SWALLOWED. ASPIRATION HAZARD - CAN ENTER LUNGS AND CAUSE DAMAGE. HARMFUL IF INHALED. MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION. OVEREXPOSURE MAY CAUSE LIVER, KIDNEY DAMAGE. CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. POTENTIAL CANCER HAZARD. CONTAINS FORMALDEHYDE WHICH HAS BEEN SHOWN TO CAUSE UPPER RESPIRATORY TRACT CANCER AND ALLERGIC RESPIRATORY REACTION. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. NOTICE: This product contains solvents. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. DANGER - Rags, steel wool or waste soaked with DS476-0910 may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water-filled metal container. For emergency information call (800) 545-2643. Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information. If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. FIRST AID: For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15

SHIPPING

FREIGHT CLASSIFICATION:

Paint, Freezable

PACKAGING: 1 gallon (3.785 L) 5 gallons (18.925 L) FLASH POINT: None

DS476-0910





to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. KEEP FROM FREEZING.

LIMITATION OF LIABILITY To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.

Akzo Nobel Paints LLC, Strongsville, Ohio 44136

FLD150-2b - 9/12 Page 2 of 2