



WONDER-PURE® Interior Primer DRN3160

FINISHES
PAINTING (09900)
9

DESCRIPTION

Our premium quality, no-VOC* (volatile organic compounds) wall primer, **WONDER-PURE®** interior primer is specially formulated to be environmentally friendly, free of odor and less likely to cause allergic sensitivity. With superior performance, **WONDER-PURE** interior primer provides exceptional hiding and sealing. This primer has excellent enamel holdout, providing a smooth, even finish coat. Fast dry and no-odor makes this product ideal for occupied environments, allowing immediate return to service. Backed by third-party certifications, **WONDER-PURE** interior primer is ideal for homes, schools, hospitals, hotels and offices.

* Testing concluded that V.O.C. levels were below accurate level of determination using EPA Test Method 24.

FEATURES

- Free Of Offensive Paint Odors
- Zero VOC Technology (untinted)
- Excellent Hiding
- Excellent sealing and enamel holdout
- Superior Adhesion
- Meets LEED Standard GS-11 (USGBC)



- **Greenguard Certified.** All Greenguard Indoor Air Quality Certified products can be used with the confidence that they will not pollute the indoor air with high levels of harmful chemicals.
- **GREENGUARD Children & SchoolsSM Certification:** Products certified under the GREENGUARD Children & Schools are ideal for use in educational, learning and play environments for your children based on its low emission rating.

COMPOSITION

- Vinyl-Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

SPECIFICATION DATA

Color:
White

Finish:
Flat

Clean-up Solvent:
Soap & water

Density:
11.03 lbs/gal (1.33 kg/L)

VOC:
0 g/L (0.0 lbs/gal)
per EPA Reference Test Method 24

Solids:
Volume - 32% +/- 1%
Weight - 49% +/- 1%

Practical Coverage:
Apply at 300-400 sq ft/gal (7-10 m²/L).
Actual coverage may vary depending on substrate and application method.

Flame Spread Rating:
Class A (0-25) over non-combustible surfaces

Flash Point:
None

Dry Time 77°F (25°C) & 50% RH:
To touch – 1 hour
To recoat – 4 hours

Shelf Life:
1 year minimum - unopened



FINISHES
PAINTING (09900)
9



SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances.

NEW SURFACES: Drywall - Prime with this product.

Wood - Sand smooth and dust clean. Prime with this product. **Concrete, Masonry and Plaster** - Cure at least 30 days before painting. pH must be 10.0 or lower. Roughen slick poured or precast concrete and remove sealers by chemical cleaning or abrasive method such as sandsweeping. Rinse thoroughly with water and allow to dry. Must be internally dry. Remove loose aggregate. Prime with this product. Fill concrete block with latex block filler DV 52903. **Steel, Galvanized Metal and Aluminum** - Prime with waterborne metal primer DP 8502 or solventborne metal primer DP 279XX. **Vinyl Wallcovering** - Do not use over vinyl wallcovering.

PREVIOUSLY PAINTED SURFACES: Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Dull glossy areas by light sanding. Remove sanding dust. Remove loose paint. Prime bare areas with primer specified under **NEW SURFACES**. Prime surface with this product.

WARNING If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

DIRECTIONS FOR USE

TINTING: May be tinted with up to two oz/gal of ICI Paints Colorants. When tinting, you will be adding small amounts of VOC's. Approximately 0.1 lbs/gal (10 g/L) with each ounce of colorant added per gallon. By comparison to conventional latex paints this is a very small amount and will not effect the low odor features of this paint. The product will still have low odor during application and virtually no residual odor after the job is complete.

SPREADING RATE: Apply at 300-400 sq. ft./gallon (7-10 m²/L). Actual coverage may vary depending on substrate and application method. For best hiding, tint primers towards finish coat color. Certain shades of yellow, orange, pink and red may require multiple coats.

APPLICATION: Mix thoroughly before use. May be

applied by brush, roller or spray. No thinning required. For airless spray application, use a .015-.017" tip. Adjust pressure as needed. If painting will be interrupted for more than 15 minutes, keep brushes and rollers wet by wrapping them with tinfoil or plastic wrap. This will prevent the paint from drying in the equipment and will make clean up much easier when the job is finished. Do not apply when the surface or air temperature is below 45°F (7°C). Provide good ventilation and warmth for normal drying.

DRYING TIME: At 77°F (25°C) and 50% R.H., dries to touch in 30-60 minutes and to recoat in two to four hours. Low temperature, high humidity, thick films or poor ventilation will increase these times.

CLEAN-UP: Clean immediately with warm, soapy water.

PRECAUTIONS

WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. For emergency information call (800) 545-2643. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** If sanding, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. Avoid contact with eyes and skin. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **KEEP FROM FREEZING.** DS10-1005

SHIPPING

FREIGHT CLASSIFICATION:
Paint, Freezable

PACKAGING:
4 quart (0.9168 L)
1 gallon (3.785 L)
5 gallons (18.925 L)

FLASH POINT:
None



ICI Paints, Strongsville, Ohio 44136



1-888-681-6353 • www.devoepaint.com

LIMITATION OF LIABILITY To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.