MATERIAL SAFETY DATA SHEET

THE FLOOD COMPANY P O BOX 2535 HUDSON OHIO 44236-0035
PH: 1-800-321-3444 FAX: 330-650-1453

FLOODPRO SUPREME PERFORMANCE

SECTION I - PRODUCT IDENTIFICATION

NAME OF MANUFACTURER	The Flood Company 1212 Barlow Road P.O. Box 2535 Hudson, Ohio 44235-0035 U.S.A
EMERGENCY TELEPHONE NO.	800-321-3444 or your local poison control center
TRANSPORTATION	Chemtrec (800) 424-9300 (24 hours)
PRODUCT NAME	FloodPro Supreme Performance All Tones
PRODUCT CLASS	Transparent water soluble wood treatment
PREPARATION DATE	9/1/05 new
DATE OF CHANGE	12/1/05 revised
PREPARED BY	Safety & Compliance Officer

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	PER-CENT	OCCUPATIONAL EXPOSURE LIMIT TLV PEL	VAPOR PRESSURE	LD50 ORAL - RAT	LC50 IHL -RAT
Acrylic Hybrid Dispersion CAS # Proprietary	< 7.0	None established	N/A	N/A	N/A
2-Butoxyethanol CAS# 111-76-2	<2.0	20ppm (ACGIH TLV) 50ppm (OSHA PEL)	0.8 @ 20C	470 mg/Kg	450 ppm/4Hr
Ethylene Glycol CAS# 107-21-1	<2.0	50ppm (ACGIH)	<.05mm Hg@ 74°F	4700 mg/kg	N/A
Non- haz inerts	>85	NA	NA	NA	NA

SECTION III - PHYSICAL DATA

BOILING RANGE	200 DEGREES F.
VAPOR DENSITY	HEAVIER THAN AIR
EVAPORATION RATE	SLOWER THAN ETHER
VOLATILE VOLUME	92%
WEIGHT/GALLON	8.45 LBS/GAL
PHYSICAL STATE	LIQUID
APPEARANCE & ODOR	Transparent earthtones, pungent odor
ODOR THRESHOLD	NOT AVAILABLE
FREEZING POINT	30°F
pH	8.0

MATERIAL SAFETY DATA SHEET

THE FLOOD COMPANY P O BOX 2535 HUDSON OHIO 44236-0035
PH: 1-800-321-3444 FAX: 330-650-1453

FLOODPRO SUPREME PERFORMANCE

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: > 200° F T.C.C. 210° F T.O.C. LEL: NOT ESTABLISHED
EXTINGUISHING MEDIA: (X) FOAM ( ) ALCOHOL FOAM (X) CO2
(X) DRY CHEMICAL (X) WATER FOG ( ) OTHER
UPPER FLAMMABLE LIMIT: NOT AVAILABLE
LOWER FLAMMABLE LIMIT: NOT AVAILABLE
UNUSUAL FIRE AND EXPLOSION HAZARDS: Product will flash at over 200 degrees F; however, product solvent is mainly water which will delay any burning unless extremely high temperatures are reached.
SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used.

SECTION V - TRANSPORTATION DATA

DOT/IMDG/IATA - Not regulated by any mode of transport.

SECTION VI - TOXICOLOGICAL PROPERTIES

EFFECTS OF OVEREXPOSURE:

SKIN: Prolonged contact may cause skin irritation or dermatitis.
EYE: Prolonged contact may cause eye irritation. Symptoms include redness, stinging, tearing.
INHALATION: No specific information. Prolonged contact may cause nose and throat irritation, headache, nausea, dizziness.
SWALLOWING: Swallowing large amounts may cause gastrointestinal irritation and discomfort, causing nausea, vomiting. Ingesting large amounts of ethylene glycol causes liver and kidney damage.

None of the ingredients of this mixture are listed as a carcinogen or potential carcinogen by the National Toxicology Program (NTP), International Agency for Research on Cancer (IARC), or the Occupational Safety and Health Administration (OSHA).

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Preexisting eye, skin, and respiratory disorders may be aggravated by exposure to this product.

PRIMARY ROUTE (S) OF ENTRY: (X) DERMAL (X) INHALATION (X) INGESTION (X) EYE

SECTION VII - FIRST AID PROCEDURES

SKIN: Wash affected area with soap and water, flush with large amounts of water.
EYE: Flush immediately with large amounts of clean cool water for at least 15 minutes. If irritation persists, get medical attention.
INHALATION: Remove victim to fresh air. Seek medical attention if symptoms persist.
SWALLOWING: If large amounts are swallowed or if irritation occurs, seek medical attention. Drink one or two glasses of water. Do not induce vomiting or give anything by mouth to an unconscious person.

MATERIAL SAFETY DATA SHEET

THE FLOOD COMPANY P O BOX 2535 HUDSON OHIO 44236-0035
PH: 1-800-321-3444 FAX: 330-650-1453

FLOODPRO SUPREME PERFORMANCE

SECTION VIII - REACTIVITY DATA

STABILITY: ( ) UNSTABLE (X) STABLE
HAZARDOUS POLYMERIZATION: ( ) MAY OCCUR (X) WILL NOT OCCUR
HAZARDOUS DECOMPOSITION PRODUCTS: Thermal deposition may generate carbon monoxide and carbon dioxide.
CONDITIONS TO AVOID: High heat storage.
INCOMPATIBILITY (MATERIALS TO AVOID): Stable under normal conditions of use. Avoid contact with strong oxidizers, strong acids.

SECTION IX - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Contain spill and, pick up with absorbent material. Place spent absorbent into an appropriate container for disposal. Large spills: Dike area of spill and pump liquid into salvage tank. Keep out of drains and waterways.
WASTE DISPOSAL METHOD: Dispose in accordance with applicable federal, state and local regulations.

SECTION X - PREVENTATIVE MEASURES

RESPIRATORY PROTECTION: NIOSH/MSHA approved respirator for concentrations up to ten times the exposure limits. For higher concentrations and emergency conditions (i.e. fire), use positive pressure, self contained breathing apparatus.
VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).
PROTECTIVE GLOVES: Impervious gloves.
EYE PROTECTION: Goggles with side shields when spraying or where splashing is likely.
OTHER PROTECTIVE EQUIPMENT: As needed. Engineering or administrative controls should be implemented to reduce exposure.
HYGIENIC PRACTICES: Wash hands with soap and water before eating, drinking, smoking, or using toilet facilities.

SECTION XI - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Avoid prolonged contact with skin. Avoid inhalation of mists. Avoid ingestion. Keep container closed when not in use.

OTHER PRECAUTIONS: Do not freeze or store near source of heat.

SECTION 313 - SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

CAS #	Chemical Name	% by Weight
107-21-1	Ethylene Glycol	<2.0
111-76-2	2-Butoxyethanol	<2.0

This information is furnished without warranty, except it is accurate to the best of The Flood Company's knowledge or obtained from sources believed to be accurate. This information is not to be construed as representation for which The Flood Company assumes legal responsibility expressed or implied.

Last update: 9/1/05 new, 11/1/05 revised section 6, 12/1/05 Minor correction to section II.