

MATERIAL SAFETY DATA SHEET

#1228

AKZO NOBEL COATINGS, INC. 1212 BARLOW ROAD HUDSON OHIO 44236 - 0035

PH: 1-800-321-3444 FAX: 330-650-1453

SPA-N-DECK BASE COAT 200VOC

SECTION I - PRODUCT IDENTIFICATION

NAME OF MANUFACTURER Akzo Nobel Coatings, Inc.
1212 Barlow Road
P.O. Box 2535
Hudson, Ohio 44236-0035 U.S.A.

EMERGENCY TELEPHONE NO. 800-321-3444 or your local poison control center
TRANSPORTATION Chemtrec @ (800) 424-9300 (24 hours)

PRODUCT NAME SPA-N-DECK BASE COAT
PRODUCT CLASS Wood Finish primer

DATE OF PREPARATION 2/1/2008
DATE OF CHANGE New
PREPARED BY HSE Coordinator

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT Chemical Name Common Name	PER- CENT	OCCUPATIONAL EXPOSURE LIMIT TLV PEL	VAPOR PRESSURE	LD50 oral -rat	LC50 lhl- rat
Petroleum Distillates Stoddard Solvent CAS # 64742-47-8	<5	100ppm 500ppm	1.0mm Hg @ 70° F	N/A	N/A
Ethylene Glycol CAS #107-21-1	<5	50 ppm (ACGIH)	<0.05 mmHG	4700 mg/kg	N/A
2,2,4-trimethyl-1,3- pentanediol monoisobutyrate Texanol CAS #25265-77-4	<5	N/A N/A	<0.01mmHG @ 70 F	3200 mg/kg	>3.55 mg/l 6 hrs

SECTION III - PHYSICAL DATA

BOILING POINT 212 DEGREES F.
VAPOR DENSITY N/A
EVAPORATION RATE SLOWER THAN ETHER
VOLATILE VOLUME 81%
WEIGHT/GALLON 8.4 LBS/GAL
PHYSICAL STATE LIQUID
APPEARANCE & ODOR Gold liquid with mild, slightly sweet aroma
ODOR THRESHOLD N/A
FREEZING POINT 32° F
pH 8.2

MATERIAL SAFETY DATA SHEET

#1228

AKZO NOBEL COATINGS, INC. 1212 BARLOW ROAD HUDSON OHIO 44236 - 0035

PH: 1-800-321-3444 FAX: 330-650-1453

SPA-N-DECK BASE COAT 200VOC

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >175° F. T.C.C. LEL: NOT ESTABLISHED
EXTINGUISHING MEDIA: (X) FOAM () ALCOHOL FOAM (X) CO2
(X) DRY CHEMICAL (X) WATER FOG () OTHER
UPPER FLAMMABLE LIMIT: NOT AVAILABLE
LOWER FLAMMABLE LIMIT: NOT AVAILABLE

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible. Exposure of closed containers to heat can cause disruptive pressure. Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Do not flush into public sewer system.

SPECIAL FIREFIGHTING PROCEDURES: Avoid breathing fumes. Wear adequate respiratory protection. Water may be ineffective as extinguishing medium but may be used to cool closed containers exposed to heat. Respiratory protection should be self-contained, breathing apparatus type with a full face piece operated in a pressure demand or other positive pressure mode.

SECTION V - TRANSPORTATION DATA

DOT - COMBUSTIBLE LIQUID

Not regulated by ground transportation in non-bulk packaging (450L or 119 gallons or less) per 49 CFR 173.150 (f)(2).

SECTION VI - TOXICOLOGICAL PROPERTIES

EFFECTS OF OVEREXPOSURE:

SKIN: May cause skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in dermatitis.

EYE: May cause eye irritation. Symptoms include stinging, tearing, redness.

INHALATION: Prolonged or repeated contact can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation.

SWALLOWING: Can cause gastrointestinal irritation, vomiting. Aspiration (breathing of vomitus into lungs must be avoided; can enter lungs and cause severe damage. Ingesting large amounts of ethylene glycol causes liver and kidney damage.

None of the ingredients of this mixture are listed as a carcinogen or potential carcinogen by the National Toxicology Program (NTP), International Agency for Research on Cancer (IARC), or the Occupational Safety and Health Administration (OSHA).

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Preexisting eye, skin, and respiratory disorders may be aggravated by exposure to this product

PRIMARY ROUTE (S) OF ENTRY: (X) DERMAL (X) INHALATION () INGESTION (X) EYE

SECTION VII - FIRST AID PROCEDURES

SKIN: Wash affected area with soap and water, flush with large amounts of water. If irritation persists, get medical attention. Do not continue to wear oil-soaked clothing. Discard oil-soaked leather goods.

EYE: Flush immediately with large amounts of water for at least 15 minutes while holding eyelids open. Get medical attention.

MATERIAL SAFETY DATA SHEET

#1228

AKZO NOBEL COATINGS, INC. 1212 BARLOW ROAD HUDSON OHIO 44236 - 0035

PH: 1-800-321-3444 FAX: 330-650-1453

SPA-N-DECK BASE COAT 200VOC

INHALATION: Remove victim to fresh air. Seek medical attention if symptoms persist.

SWALLOWING: DO NOT INDUCE VOMITING due to danger of aspirating oil into the lungs. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. **DO NOT** give anything by mouth if the person is unconscious or having convulsions. Get medical attention immediately.

NOTE TO PHYSICIAN: Aspiration of liquid petroleum products into lungs may cause severe pneumonitis (oil pneumonia). Vomiting should not be induced.

SECTION VIII- REACTIVITY DATA

STABILITY: () UNSTABLE (X) STABLE

HAZARDOUS POLYMERIZATION: () MAY OCCUR (X) WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion in restricted environments can produce carbon monoxide, carbon dioxide and various hydrocarbons.

CONDITIONS TO AVOID: Storage of combustible materials wetted with liquid can produce heat and spontaneous combustion.

INCOMPATIBILITY (MATERIALS TO AVOID): Stable under normal conditions of use. Avoid contact with strong oxidizers.

SECTION IX- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of vapor ignitions. Ventilate area. Stop spill at source. **SMALL SPILL:** Remove liquid waste with oil-absorbing compounds and non-sparking tools. **LARGE SPILL:** Exclude persons not wearing protective equipment, dike area of spill and pump liquid into salvage tank.

WASTE DISPOSAL METHOD: Do not incinerate closed containers. Do not dispose of waste material in sewers or waterways. Promptly incinerate wetted, combustible, oil-absorbing materials. Dispose in accordance with all local, State and Federal regulations.

SECTION X - PREVENTATIVE MEASURES

RESPIRATORY PROTECTION: If TLV of the product or any component is exceeded, a NIOSH/OSHA jointly approved, air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/OSHA respirators under specified conditions (see your safety equipment supplier). Engineering or administrative controls should be implemented to reduce exposure.

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

PROTECTIVE GLOVES: Oil resistant if prolonged liquid contact is likely.

EYE PROTECTION: Goggles with side shields when spraying or where splashing is likely.

OTHER PROTECTIVE EQUIPMENT: Oil repellent, protective clothing if prolonged liquid contact is likely.

HYGIENIC PRACTICES: Wash hands with soap and water thoroughly after use. Launder contaminated clothing before reuse.

SECTION XI - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: **COMBUSTIBLE.** Prevent contact with flames or hot surfaces. Do not store near heat. Keep containers closed when not in use. Avoid prolonged contact with skin. Avoid breathing concentrated vapors.

OTHER PRECAUTIONS: Store only in well-ventilated areas. Store out of sun and away from heat.

MATERIAL SAFETY DATA SHEET

#1228

AKZO NOBEL COATINGS, INC. 1212 BARLOW ROAD HUDSON OHIO 44236 - 0035

PH: 1-800-321-3444 FAX: 330-650-1453

SPA-N-DECK BASE COAT 200VOC

DANGER:

Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent this.

SECTION 313 - SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

<u>CAS#</u>	<u>Chemical Name</u>	<u>% by Weight</u>
107-21-1	Ethylene Glycol	<5.0

This information is furnished without warranty, except it is accurate to the best of Akzo Nobel Coatings, Inc.'s knowledge or obtained from sources believed to be accurate. This information is not to be construed as representation for which Akzo Nobel Coatings, Inc. assumes legal responsibility expressed or implied.

MATERIAL SAFETY DATA SHEET

#1222

AKZO NOBEL COATINGS, INC. 1212 BARLOW ROAD HUDSON OHIO 44236 - 0035

PH: 1-800-321-3444 FAX: 330-650-1453

SPA-N-DECK BASE COAT (315VOC)

SECTION I - PRODUCT IDENTIFICATION

NAME OF MANUFACTURER Akzo Nobel Coatings, Inc.
1212 Barlow Road
P.O. Box 2535
Hudson, Ohio 44236-0035 U.S.A.

EMERGENCY TELEPHONE NO. 800-321-3444 or your local poison control center
TRANSPORTATION Chemtrec @ (800) 424-9300 (24 hours)

PRODUCT NAME SPA-N-DECK BASE COAT 315VOC
PRODUCT CLASS Wood Finish primer

DATE OF PREPARATION 02/14/02
DATE OF CHANGE 2/1/08
PREPARED BY HSE Coordinator

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	PER-CENT	OCCUPATIONAL EXPOSURE LIMIT TLV	VAPOR PRESSURE	LD50 oral -rat	LC50 lhl- rat
Chemical Name Common Name Petroleum Distillates Stoddard Solvent CAS # 64742-47-8	<5	100ppm 500ppm	1.0mm Hg @ 70° F	N/A	N/A
Ethylene Glycol CAS #107-21-1	<5	50 ppm (ACGIH)	<0.05 mmHG	4700 mg/kg	N/A
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate Texanol CAS #25265-77-4	<5	N/A N/A	<0.01mmHG @ 70 F	3200 mg/kg	>3.55 mg/l 6 hrs

SECTION III - PHYSICAL DATA

BOILING POINT 212 DEGREES F.
VAPOR DENSITY N/A
EVAPORATION RATE SLOWER THAN ETHER
VOLATILE VOLUME 81%
WEIGHT/GALLON 8.4 LBS/GAL
PHYSICAL STATE LIQUID
APPEARANCE & ODOR Gold liquid with mild, slightly sweet aroma
ODOR THRESHOLD N/A
FREEZING POINT 32° F
pH 8.2

MATERIAL SAFETY DATA SHEET

#1222

AKZO NOBEL COATINGS, INC. 1212 BARLOW ROAD HUDSON OHIO 44236 - 0035

PH: 1-800-321-3444 FAX: 330-650-1453

SPA-N-DECK BASE COAT (315VOC)

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >175° F. T.C.C. LEL: NOT ESTABLISHED

EXTINGUISHING MEDIA: (X) FOAM () ALCOHOL FOAM (X) CO2

(X) DRY CHEMICAL (X) WATER FOG () OTHER

UPPER FLAMMABLE LIMIT: NOT AVAILABLE

LOWER FLAMMABLE LIMIT: NOT AVAILABLE

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible. Exposure of closed containers to heat can cause disruptive pressure. Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Do not flush into public sewer system.

SPECIAL FIREFIGHTING PROCEDURES: Avoid breathing fumes. Wear adequate respiratory protection. Water may be ineffective as extinguishing medium but may be used to cool closed containers exposed to heat. Respiratory protection should be self-contained, breathing apparatus type with a full face piece operated in a pressure demand or other positive pressure mode.

SECTION V - TRANSPORTATION DATA

DOT - COMBUSTIBLE LIQUID

Not regulated by ground transportation in non-bulk packaging (450L or 119 gallons or less) per 49 CFR 173.150 (f)(2).

SECTION VI - TOXICOLOGICAL PROPERTIES

EFFECTS OF OVEREXPOSURE:

SKIN: May cause skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in dermatitis.

EYE: May cause eye irritation. Symptoms include stinging, tearing, redness.

INHALATION: Prolonged or repeated contact can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation.

SWALLOWING: Can cause gastrointestinal irritation, vomiting. Aspiration (breathing of vomitus into lungs must be avoided); can enter lungs and cause severe damage. Ingesting large amounts of ethylene glycol causes liver and kidney damage.

None of the ingredients of this mixture are listed as a carcinogen or potential carcinogen by the National Toxicology Program (NTP), International Agency for Research on Cancer (IARC), or the Occupational Safety and Health Administration (OSHA).

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Preexisting eye, skin, and respiratory disorders may be aggravated by exposure to this product

PRIMARY ROUTE (S) OF ENTRY: (X) DERMAL (X) INHALATION () INGESTION (X) EYE

SECTION VII - FIRST AID PROCEDURES

SKIN: Wash affected area with soap and water, flush with large amounts of water. If irritation persists, get medical attention. Do not continue to wear oil-soaked clothing. Discard oil-soaked leather goods.

EYE: Flush immediately with large amounts of water for at least 15 minutes while holding eyelids open. Get medical attention.

MATERIAL SAFETY DATA SHEET

#1222

AKZO NOBEL COATINGS, INC. 1212 BARLOW ROAD HUDSON OHIO 44236 - 0035

PH: 1-800-321-3444 FAX: 330-650-1453

SPA-N-DECK BASE COAT (315VOC)

INHALATION: Remove victim to fresh air. Seek medical attention if symptoms persist.

SWALLOWING: DO NOT INDUCE VOMITING due to danger of aspirating oil into the lungs. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. **DO NOT** give anything by mouth if the person is unconscious or having convulsions. Get medical attention immediately.

NOTE TO PHYSICIAN: Aspiration of liquid petroleum products into lungs may cause severe pneumonitis (oil pneumonia). Vomiting should not be induced.

SECTION VIII- REACTIVITY DATA

STABILITY: () UNSTABLE (X) STABLE

HAZARDOUS POLYMERIZATION: () MAY OCCUR (X) WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion in restricted environments can produce carbon monoxide, carbon dioxide and various hydrocarbons.

CONDITIONS TO AVOID: Storage of combustible materials wetted with liquid can produce heat and spontaneous combustion.

INCOMPATIBILITY (MATERIALS TO AVOID): Stable under normal conditions of use. Avoid contact with strong oxidizers.

SECTION IX- SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of vapor ignitions. Ventilate area. Stop spill at source. **SMALL SPILL:** Remove liquid waste with oil-absorbing compounds and non-sparking tools. **LARGE SPILL:** Exclude persons not wearing protective equipment, dike area of spill and pump liquid into salvage tank.

WASTE DISPOSAL METHOD: Do not incinerate closed containers. Do not dispose of waste material in sewers or waterways. Promptly incinerate wetted, combustible, oil-absorbing materials. Dispose in accordance with all local, State and Federal regulations.

SECTION X - PREVENTATIVE MEASURES

RESPIRATORY PROTECTION: If TLV of the product or any component is exceeded, a NIOSH/OSHA jointly approved, air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/OSHA respirators under specified conditions (see your safety equipment supplier). Engineering or administrative controls should be implemented to reduce exposure.

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

PROTECTIVE GLOVES: Oil resistant if prolonged liquid contact is likely.

EYE PROTECTION: Goggles with side shields when spraying or where splashing is likely.

OTHER PROTECTIVE EQUIPMENT: Oil repellent, protective clothing if prolonged liquid contact is likely.

HYGIENIC PRACTICES: Wash hands with soap and water thoroughly after use. Launder contaminated clothing before reuse.

SECTION XI - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: **COMBUSTIBLE.** Prevent contact with flames or hot surfaces. Do not store near heat. Keep containers closed when not in use. Avoid prolonged contact with skin. Avoid breathing concentrated vapors.

OTHER PRECAUTIONS: Store only in well-ventilated areas. Store out of sun and away from heat.

DANGER:

MATERIAL SAFETY DATA SHEET

#1222

AKZO NOBEL COATINGS, INC. 1212 BARLOW ROAD HUDSON OHIO 44236 - 0035

PH: 1-800-321-3444 FAX: 330-650-1453

SPA-N-DECK BASE COAT (315VOC)

Rags, steel wool or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags, steel wool or waste in a sealed water filled metal container to prevent this.

SECTION 313 - SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

<u>CAS#</u>	<u>Chemical Name</u>	<u>% by Weight</u>
107-21-1	Ethylene Glycol	<5.0

This information is furnished without warranty, except it is accurate to the best of Akzo Nobel Coatings, Inc.'s knowledge or obtained from sources believed to be accurate. This information is not to be construed as representation for which Akzo Nobel Coatings, Inc. assumes legal responsibility expressed or implied.

Changes:

3/1/04 Section II, XI – Section 313

2/1/08 Manufacturer name change.

MATERIAL SAFETY DATA SHEET MSDS #1221
 AKZO NOBEL COATINGS, INC. 1212 BARLOW ROAD HUDSON OHIO 44236 - 0035
 PH: 1-800-321-3444 FAX: 330-650-1453

SPA-N-DECK FINISH
 WOODTONES

SECTION I - PRODUCT IDENTIFICATION					
NAME	AKZO NOBEL COATINGS, INC. 1212 Barlow Road P.O. Box 2535 Hudson, Ohio 44236-0035 USA				
EMERGENCY TELEPHONE NO.	800-321-3444 or your local poison control center				
TRANSPORTATION	(CHEMTREC): 800- 424-9300 (24 hours)				
PRODUCT NAME	SPA-N-DECK FINISH				
PRODUCT CLASS	Acrylic Exterior Wood Finish				
PREPARATION DATE	December 17, 1999				
REVISION DATE	2/1/08				
PREPARED BY	HSE Coordinator				
SECTION II - Composition / Information on Ingredients					
INGREDIENT(S)	%	Occupational	Vapor	LD50	LC50
Chemical Name	Weight	Exposure Limits	Pressure	Oral	Inhal
Common Name		TLV PEL		Rat	Rat
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate Texanol CAS # 25265-77-4	< 5	None established	< 0.01 mmHG	3200 mg/kg	> 3.55 mg/l 6 hrs
Ethylene Glycol CAS# 107-21-1	< 5	50ppm (ACGIH)	<0.05 mmHG	4700 mg/kg	N/A
Water/Inerts/Acrylic Polymer	> 75	N/A	N/A	N/A	N/A
SECTION III - PHYSICAL DATA					
BOILING RANGE	200 DEGREES F.				
VAPOR DENSITY	LIGHTER THAN AIR				
EVAPORATION RATE	SLOWER THAN ETHER				
VOLATILE VOLUME	85.66				
WEIGHT/GALLON	8.61 LBS/GAL				
PHYSICAL STATE	LIQUID				
APPEARANCE & ODOR	COLOR DEPENDENT ON PIGMENT				
ODOR THRESHOLD	NOT AVAILABLE				
FREEZING POINT	30°F				
pH	8.5 - 9.5				
VOC CONTENT	<275 g/L				

SPA-N-DECK FINISH
 WOODTONES

SECTION IV - FIRE AND EXPLOSION HAZARD DATA
FLASH POINT: > 200° F LEL: NOT ESTABLISHED EXTINGUISHING MEDIA: (X) FOAM () ALCOHOL FOAM (X) CO2 (X) DRY CHEMICAL (X) WATER FOG () OTHER UPPER FLAMMABLE LIMIT: NOT AVAILABLE LOWER FLAMMABLE LIMIT: NOT AVAILABLE UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may burst if exposed to extreme heat or fire. SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used. Wear self-contained breathing apparatus and full protective gear
SECTION V - TRANSPORTATION DATA
DOT - NOT REGULATED
SECTION VI - TOXICOLOGICAL PROPERTIES
EFFECTS OF OVEREXPOSURE: INHALATION: Short-term harmful effects are not expected from vapor. Prolonged exposure may lead to mild and temporary respiratory irritation. SKIN: May cause mild skin irritation. EYE: May cause mild eye irritation or discomfort. INGESTION: Swallowing large amounts may cause abdominal discomfort, nausea, vomiting. Ingesting large amounts of ethylene glycol causes liver and kidney damage. None of the ingredients of this mixture is listed as a human carcinogen by the National Toxicology Program (NTP), International Agency for Research on Cancer (IARC), or the Occupational Safety and Health Administration (OSHA). MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: Available toxicology information along with physical and chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions. PRIMARY ROUTE (S) OF ENTRY: (X) DERMAL () INHALATION (X) INGESTION (X) EYE
SECTION VII - FIRST AID PROCEDURES
SKIN: Wash affected area with soap and water, flush with large amounts of water. INHALATION: Remove victim to fresh air. Seek medical attention if symptoms persist. EYES: Flush immediately with large amounts of clean cool water for at least 15 minutes. If irritation persists, get medical attention. SWALLOWING: If large amounts are swallowed or if irritation occurs, seek medical attention. Drink one or two glasses of water. Do not induce vomiting or give anything by mouth to an unconscious person.
SECTION VIII - REACTIVITY DATA

SPA-N-DECK FINISH
WOODTONES

STABILITY: () UNSTABLE (X) STABLE
HAZARDOUS POLYMERIZATION: () MAY OCCUR (X) WILL NOT OCCUR
HAZARDOUS DECOMPOSITION PRODUCTS: Thermal deposition may generate carbon monoxide and carbon dioxide.
CONDITIONS TO AVOID: Temperatures above 190 F and below 40 F.
INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with strong oxidizing agents.

SECTION IX - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Contain spill and pick up with absorbent material.
WASTE DISPOSAL METHOD: Dispose in accordance with applicable federal, state and local regulations.

SECTION X - PREVENTATIVE MEASURES

RESPIRATORY PROTECTION: None needed under normal conditions. If spray applying and/or vapors, mists or aerosols are generated, additional protection may be obtained by wearing a NIOSH/MSHA approved respirator.
VENTILATION: Use with adequate ventilation.
PROTECTIVE GLOVES: Impervious gloves, to minimize contact.
EYE PROTECTION: Goggles with side shields when spraying or where splashing is likely.
OTHER PROTECTIVE EQUIPMENT: None needed with normal use.
HYGIENIC PRACTICES: Wash hands with soap and water before eating, drinking, smoking, or using toilet facilities.

SECTION XI - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep container closed when not in use. Store at room temperature, maximum recommended storage is 120 F. Do not freeze or store near source of heat.
OTHER PRECAUTIONS: It is always good industrial hygiene practice to minimize contact with eye and skin. Wash thoroughly with soap and water when finished.

SECTION 313 - SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

<u>CAS #</u>	<u>Chemical Name</u>	<u>% by Weight</u>
107-21-1	Ethylene glycol	<5.0

This information is furnished without warranty, except it is accurate to the best of AKZO NOBEL COATINGS, INC.'s knowledge or obtained from sources believed to be accurate. This information is not to be construed as representation for which AKZO NOBEL COATINGS, INC. assumes legal responsibility expressed or implied.

CHANGES:

5/2/02 to sections II, III, VI and XI - Section 313
2/1/08 Manufacturer name change