



# Paints

## PREP & PRIME™ PVA WALL Interior Water-Based Primer 1030-1200

### SPECIFICATION DATA

Our good quality latex primer for use under latex or alkyd paints on properly prepared new or previously painted drywall, concrete block and brick. Easy application by brush, roller or airless spray resulting in excellent sealing and holdout properties. Dries quickly to proper hardness for easy sanding. Ideal for use on new and existing residential construction and commercial structures such as schools, offices, hotels and hospitals.

### FEATURES

- Easy application
- Fast drying
- High Hiding
- Easy soap and water clean-up
- Low odor
- Low VOC
- Performance alternate for Federal Paint Specification TT-P-650D

### COMPOSITION

- Vinyl Acrylic Resin
- Titanium Dioxide and Extender Pigments
- Not manufactured with lead or mercury containing materials.

### DESCRIPTION

**Color:**  
White (tintable, limit 4 oz/gal)

**Finish:**  
Flat

**Clean-up Solvent:**  
Soap and water

**Density:**  
10.5 lbs/gal (1.26 kg/L)

**VOC:**  
0.84 lbs/gal (100 g/L)

**Solids:**  
Volume - 26% ± 1%  
Weight - 41% ± 1%

**Practical Coverage:**  
Apply at 400 sq ft/gal (10 m<sup>2</sup>/L).  
Actual coverage may vary depending on substrate and application method.

**Flame Spread Rating:**  
Class A (0-25) over non-combustible surfaces

**Flash Point:**  
None

**Dry Time 77°F (25°C) & 50% RH:**  
To touch - 30 minutes  
To recoat - 2 hours

**Shelf Life:**  
1 year minimum - unopened

FINISHES  
PAINTING (09900)

9



Paints



FINISHES  
PAINTING (09900)

9

## SURFACE PREPARATION

All surfaces must be sound, dry, clean and free of oil, grease, dirt, mildew, form release agents, curing compounds, loose and flaking paint and other foreign substances.

**NEW SURFACES:** Drywall - Prime with this product.

**Concrete, Masonry and Plaster** - Cure at least 30 days before painting. pH must be 10.0 or lower. Roughen slick poured or precast concrete and remove sealers by chemical cleaning or abrasive method such as sandsweeping. Rinse thoroughly with water and allow to dry. Remove loose aggregate. Prime with this product or PREP & PRIME GRIPPER MULTI-PURPOSE 3210 water-based primer sealer. Fill block with PREP & PRIME BLOCK FILLER 3010 water-based block filler or BLOXFIL 4000 acrylic block filler. Prime plaster with PREP & PRIME GRIPPER MULTI-PURPOSE 3210 water-based primer sealer. **Wood** - Sand smooth and dust clean. Prime with PREP & PRIME GRIPPER MULTI-PURPOSE 3210 water-based primer. **Steel** - Prime with DEVFLEX™ 4020PF water-based metal primer or DEVGUARD™ 4160 or DEVGUARD 4100 solvent-metal primer. **Galvanized Metal and Aluminum** - Prime with PREP & PRIME GRIPPER MULTI-PURPOSE 3210

water-based primer sealer or DEVFLEX™ 4020PF water-based metal primer or DEVGUARD 4160 or DEVGUARD 4120 solvent-based metal primer.

**PREVIOUSLY PAINTED SURFACES:** Wash to remove contaminants. Rinse thoroughly with water and allow to dry. Dull glossy areas by light sanding. Remove sanding dust. Remove loose paint. Prime bare areas with primer specified under **NEW SURFACES**. Porous flat finishes must be sealed with this product.

**WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**

## DIRECTIONS FOR USE

**TINTING:** May be tinted toward the finish coat color with up to four oz/gal of ICI Paints Colorants.

**SPREADING RATE:** Apply at 400 sq ft/gal (10 m<sup>2</sup>/L). Actual coverage may vary depending on substrate and application method.

**APPLICATION:** Mix thoroughly before use. May be applied by brush, roller or spray. No thinning required. For airless spray, use a .015" tip. Adjust pressure as needed. Do not apply when the surface or air temperature is below 50°F (10°C). Provide good ventilation and warmth for normal drying.

**DRYING TIME:** At 77°F (25°C) and 50% R.H., dries to touch in 30 minutes and to recoat in two hours. Low temperature, high humidity, thick films or poor ventilation will increase these times.

**CLEAN-UP:** Clean immediately with warm, soapy water.

## PRECAUTIONS

**WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. HARMFUL IF SWALLOWED. CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. CONTAINS CRYSTALLINE SILICA WHICH CAN CAUSE LUNG CANCER AND OTHER LUNG DAMAGE IF INHALED. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN. Products in this series may contain chemicals subject to California Proposition 65.** For emergency information call (800) 545- 2643. If sanding is done, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** In case of skin contact, wash off **quickly** with plenty of soap and water, remove contaminated clothing. For eye contact flush **immediately** with large amounts of water, for at least 15 minutes. **Obtain emergency medical treatment.** If swallowed, **obtain medical treatment immediately.** If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, **get medical help.** **KEEP FROM FREEZING.** **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.**

0896

DS2-

## SHIPPING

**FREIGHT CLASSIFICATION:**  
Paint, Freezable

**PACKAGING:**  
1 gallon (3.785 L)  
5 gallons (18.925 L)

**FLASH POINT:**  
None



ICI Paints, Strongsville, Ohio 44136

1-800-984-5444 • [www.icipaintsstores.com](http://www.icipaintsstores.com)

**LIMITATION OF LIABILITY** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.