



**Paints**

**GROUNDWORKS™  
Slip Resistant Additive  
3001-0000**

**DESCRIPTION**

A finely ground polymer material to be added to paint, concrete stains or sealers to achieve a slip resistant surface on walkways, driveways, garage floors, patios, pool decks and other horizontal surfaces.

**SPECIFICATION DATA**

**Color:**

White powder, transparent in clear coatings

**Density:**

0.90 g/cc

**Mean Particle Size:**

160-180 (microns)  
50 (mesh)

**FEATURES**

- Increases traction & slip resistance
- Long lasting, uniform suspension in thin bodied materials
- Can be added to water & solvent-based stains, paints & clear sealers
- Small particle size & rounded nature creates slip resistant surface that is more comfortable to bare feet
- Excellent for use on pool decks, patios, & garage floors
- Creates a subtle textured finish

**COMPOSITION**

- Micronized polypropylene
- Not manufactured with lead or mercury containing materials.



**Paints**

## DIRECTIONS FOR USE

Designed to be incorporated into a suitable paint, concrete stain or sealer. Minimum inclusion ratio of GROUNDWORKS Slip Resistant Additive 3001-0000 is as follows: 0.2 lbs (3.2oz) to a gallon can or 1.0 lbs (16oz) to a five-gallon pail. More may be added depending on the desired texturing effect, but not to exceed ½ lbs (8oz) per gallon. While continually stirring, add GROUNDWORKS Slip Resistant Additive 3001-0000 to the container of paint, concrete stain or sealer. It may tend to float at first, but once wet it will mix in easily. Occasional stirring, during application, may be required in thinner products to keep the particles well suspended within the coating. Follow application instructions of the paint, concrete stain or sealer. Use of this additive in materials should be for additional slip resistance as a safety measure and should not be used in place of a nonskid finish.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## PRECAUTIONS

**CAUTION! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.** For emergency information call (800) 545-2643. **Note: These warnings encompass the product series. Prior to use, read and follow product-specific MSDS and label information.** If sanding is done, wear a dust mask to avoid breathing of sanding dust. Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, leave the area. If properly used, a respirator may offer additional protection. Obtain professional advice before using. Close container after each use. **FIRST AID:** In case of skin contact, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. For eye contact, flush **immediately** with large amounts of water, for at least 15 minutes. **Obtain emergency medical treatment.** If swallowed, **obtain medical treatment immediately.** If inhalation causes physical discomfort, remove to fresh air. If discomfort persists or any breathing difficulty occurs, **get medical help. KEEP FROM FREEZING.**

DSS-1100

## SHIPPING

**FREIGHT CLASSIFICATION:**  
Paint, Freezable

**PACKAGING:**  
0.2 lbs.  
1 lb.

**FLASH POINT:**  
None

Distributed by:



ICI Paints, Strongsville, Ohio 44136

1-800-984-5444 • [www.icipaintsstores.com](http://www.icipaintsstores.com)

**LIMITATION OF LIABILITY** To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. WE MAKE NO OTHER WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE. Liability, if any, is limited to replacement of the product or refund of the purchase price. LABOR OR COST OF LABOR AND OTHER CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.